

Priključak s rezanim prstenom Serija C-WAS



Osnovno tijelo s maticom i rezni prsten



B4-Rezni prsten






B3-Rezni prsten

Izvedba	Priključak s rezanim prstenom, s B3 ili B4-reznim prstenom
Vanjski promjer cijevi	6...42mm
Materijal	Čelik pocinčan
prema norma	EN ISO 8434-1 (DIN 2353)
Medij	neutralne tekućine i plinovi, koji ne napadaju upotrijebljene materijale
Temperatura medija	B3-Rezni prsten -40...+120°C B4-Rezni prsten NBR -35...+100°C (FKM auf Anfrage)
Radni tlak	Nazivni tlak prema tablici



Dimenzije



Osnovno tijelo

s B4-reznim prstenom

s B3-reznim prstenom

Seriya	PN [bar]	Promjer cijevi	D1	L1	L2	L3	L4	CH1	CH2	Tip Osnovno tijelo	Tip s B4-prstenom	Tip s B3-prstenom
L	315	6	10	19	12	19	27	12	14	C-WAS06LX	C-WAS06ZL	C-WAS06L
		8	12	21	14	21	29	12	17	C-WAS08LX	C-WAS08ZL	C-WAS08L
		10	14	22	15	22	30	14	19	C-WAS10LX	C-WAS10ZL	C-WAS10L
		12	16	24	17	24	32	17	22	C-WAS12LX	C-WAS12ZL	C-WAS12L
		15	19	28	21	28	36	19	27	C-WAS15LX	C-WAS15ZL	C-WAS15L
		18	22	31	23,5	31	40	24	32	C-WAS18LX	C-WAS18ZL	C-WAS18L
	160	22	27	35	27,5	35	44	27	36	C-WAS22LX	C-WAS22ZL	C-WAS22L
		28	32	38	30,5	38	47	36	41	C-WAS28LX	C-WAS28ZL	C-WAS28L
		35	40	45	34,5	45	56	41	50	C-WAS35LX	C-WAS35ZL	C-WAS35L
		42	46	51	40	51	63	50	60	C-WAS42LX	C-WAS42ZL	C-WAS42L
S	630	6	11	23	16	23	31	12	17	C-WAS06SX	C-WAS06ZS	C-WAS06S
		8	13	24	17	24	32	14	19	C-WAS08SX	C-WAS08ZS	C-WAS08S
		10	15	25	17,5	25	34	17	22	C-WAS10SX	C-WAS10ZS	C-WAS10S
		12	17	29	21,5	29	38	17	24	C-WAS12SX	C-WAS12ZS	C-WAS12S
		14	19	30	22	30	40	19	27	C-WAS14SX	C-WAS14ZS	C-WAS14S
	400	16	21	33	24,5	33	43	24	30	C-WAS16SX	C-WAS16ZS	C-WAS16S
		20	26	37	26,5	37	48	27	36	C-WAS20SX	C-WAS20ZS	C-WAS20S
		25	31	42	30	42	54	36	46	C-WAS25SX	C-WAS25ZS	C-WAS25S
		30	36	49	35,5	49	62	41	50	C-WAS30SX	C-WAS30ZS	C-WAS30S
		315	44	57	41	57	72	50	60	C-WAS38SX	C-WAS38ZS	C-WAS38S

Ilustracije neobvezujuće

Zadržavamo pravo na konstrukcijske, dimenzijske i promjene materijala.

Pneumatika / Spojni elementi i spojnice / Rezni prstenasti priključci / Rezni prstenasti priključci - Pocičani čelik ISO 8434-1 (DIN 2353) / Kutni zavarljivi priključak Serija C-WAS

Verzija 6

138496 / Generirano 2026/33 HR

PROIZVEDENO U EUROPI

+381 11 2399521

balkan@stasto.eu

© STASTO Automatizacija d.o.o.

www.stasto.rs

Otvori seriju online

Stranica 2 / 2

