


Straight Male stud fitting made of aluminium for PVC - fabric-reinforced hose



Design type	Screw fitting with union nut and Compression ring
Connection	G1/8"...G1/2" according to ISO228/1
Tube outside diameter	10mm...21mm
Materials	Fitting complete Aluminium, Compression ring POM
recommended Tube materials	PVC - Fabric hose series PV
Medium	Gases and liquids which do not chemically attack the materials
Medium temperature	-10°C...+60°C
Operating pressure	-0,95...10bar and depending on the hose

Dimensions

	Hose diameter D / d [mm]	Connection G	L1	L2	SW	SW1	Weight [g]	Type
	10/4	G1/8"	30,5	6,5	17	17	12	CF-10/4-18-A
	10/4	G1/4"	33	9	17	17	14	CF-10/4-14-A
	10/4	G3/8"	33	9	19	17	14	CF-10/4-38-A
	10/4	G1/2"	36	11	24	17	20	CF-10/4-12-A
	12/6	G1/8"	32,5	6,5	17	19	14	CF-12/6-18-A
	12/6	G1/4"	35	9	17	19	14	CF-12/6-14-A
	12/6	G3/8"	35	9	19	19	16	CF-12/6-38-A
	12/6	G1/2"	37,5	11	24	19	22	CF-12/6-12-A
	14/8	G1/4"	38	9	22	22	23	CF-14/8-14-A
	14/8	G3/8"	38	9	22	22	23	CF-14/8-38-A
	14/8	G1/2"	40	11	24	22	27	CF-14/8-12-A
	15/9	G1/4"	38,5	9	22	24	27	CF-15/9-14-A
	15/9	G3/8"	38,5	9	22	24	27	CF-15/9-38-A
	15/9	G1/2"	40,5	11	24	24	32	CF-15/9-12-A
	16/10	G1/4"	38,5	9	22	24	27	CF-16/10-14-A
	16/10	G3/8"	38,5	9	22	24	27	CF-16/10-38-A
	16/10	G1/2"	40,5	11	24	24	31	CF-16/10-12-A
	20/13	G3/8"	41	9	27	30	46	CF-20/13-38-A
	20/13	G1/2"	43	11	27	30	48	CF-20/13-12-A
	21/12	G3/8"	41	9	27	30	45	CF-21/12-38-A
	21/12	G1/2"	43	11	27	30	48	CF-21/12-12-A

Illustrations non-binding

Design, dimensional and material changes reserved

