

## Šuplji vijci - Mjed poniklanjeno Serija TH



TH51



TH52




TH53




TH54

|                    |                                                                 |
|--------------------|-----------------------------------------------------------------|
| Izvedba            | Šuplji vijci za upotrebu s priključcima serija: DI,PI,SC,TH     |
| Priključak         | G1/8" ... G1/2" cilindrični prema ISO 228/1, M5 prema ISO R/262 |
| Materijali         | Tijelo Mjed poniklanjeno, Brtve PA                              |
| Medij              | Stlačeni zrak, neutralni plinovi                                |
| Temperatura medija | -20°C ... +70°C                                                 |
| Radni tlak         | -1...15 bar, ovisno o maksimalnom tlaku upotrijebljene cijevi   |


### TH51 1-struko Šuplji vijak

|  | D1     | L1  | L2   | L3   | CH | Težina [g] | Tip       |
|-------------------------------------------------------------------------------------|--------|-----|------|------|----|------------|-----------|
|                                                                                     | M5x0,8 | 4   | 16   | 19   | 8  | 3          | TH51-M5-N |
|                                                                                     | G1/8"  | 5   | 23   | 27   | 14 | 14         | TH51-18-N |
|                                                                                     | G1/4"  | 6,5 | 26,5 | 31,5 | 17 | 27         | TH51-14-N |
|                                                                                     | G3/8"  | 7   | 30   | 36   | 20 | 44         | TH51-38-N |
|                                                                                     | G1/2"  | 8,5 | 35,5 | 41,5 | 26 | 82         | TH51-12-N |

### TH52 2-struko Šuplji vijak

|  | D1    | L1  | L2   | L3   | CH | Težina [g] | Tip       |
|-------------------------------------------------------------------------------------|-------|-----|------|------|----|------------|-----------|
|                                                                                     | G1/8" | 5   | 39,5 | 42,5 | 14 | 20         | TH52-18-N |
|                                                                                     | G1/4" | 6,5 | 45   | 50   | 17 | 39         | TH52-14-N |
|                                                                                     | G3/8" | 7   | 51,5 | 57,5 | 20 | 63         | TH52-38-N |
|                                                                                     | G1/2" | 8,5 | 61   | 67   | 26 | 120        | TH52-12-N |

### TH53 1-struko Šuplji vijak za nadogradnju

|  | D1    | D2    | L1  | L2   | L3   | L4 | CH | Težina [g] | Tip       |
|-------------------------------------------------------------------------------------|-------|-------|-----|------|------|----|----|------------|-----------|
|                                                                                     | G1/8" | G1/8" | 5   | 23   | 35   | 8  | 14 | 20         | TH53-18-N |
|                                                                                     | G1/4" | G1/4" | 6,5 | 26,5 | 40,5 | 10 | 17 | 33         | TH53-14-N |
|                                                                                     | G3/8" | G3/8" | 7   | 30   | 45   | 11 | 20 | 48         | TH53-38-N |



## TH54 Dvostruki montažni šuplji vijak (banjo)

|  | D1    | D2    | L1  | L2   | L3   | L4 | CH | Težina [g] | Tip       |
|--|-------|-------|-----|------|------|----|----|------------|-----------|
|  | G1/8" | G1/8" | 5   | 39,5 | 51,5 | 8  | 14 | 27         | TH54-18-N |
|  | G1/4" | G1/4" | 6,5 | 45   | 59   | 10 | 17 | 44         | TH54-14-N |
|  | G3/8" | G3/8" | 7   | 51,5 | 66,5 | 11 | 20 | 67         | TH54-38-N |
|  |       |       |     |      |      |    |    |            |           |

Ilustracije neobvezujuće

Zadržavamo pravo na konstrukcijske, dimenzijske i promjene materijala.

Pneumatika / Spojni elementi i spojnice / Šuplji vijci / Brtve / Šuplji vijci - Mjed niklan - Tlak -1...15 bar

