


Spojnice DN12mm Serija C0.12-B




Konstrukcija	Utičnice spojnice i utikači spojnice, jednosmerno zatvaranje
Nazivni prečnik	DN12mm
Priključak	G1/2"...G3/4" prema ISO228/1
Materijali	Telo, ventil i konektor Mesing, Opruga od nerđajućeg čelika 1.4310, Zaptivka NBR
Nominalni protok	4000NI/min pri 6 bar (Δp 1bar)
Medij	Komprimovani vazduh i tečnosti
Temperatura medijuma	-10...+50°C
Radni pritisak	0...16bar


C0C12-M Utičnica spojnice - Spoljašnji navoj

	D1	D2	L1	L2	CH	Tip
	G1/2"	50	12	82	30	C0C12-M12-B
	G3/4"	50	12	82	30	C0C12-M34-B


C0C12-F Utičnica spojnice - Unutrašnji navoj

	D1	D2	L1	L2	CH	Tip
	G1/2"	50	12	82	30	C0C12-F12-B
	G3/4"	50	12	82	30	C0C12-F34-B

C0C12-H Utičnica spojnice - Nastavak za crevo

	Unutrašnji prečnik creva		L1	Tip
	13		87	C0P12-H13-B
	16		87	C0P12-H16-B
	19		87	C0P12-H19-B

C0P12-M Priključni utikač - Spoljašnji navoj

	D1	L1	CH	Tip
	G1/4"	54	17	C0P12-M14-B
	G1/2"	63	20	C0P12-M12-B



Ilustracije neobavezujuće
Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Spojnice / čep spojnice standard / spojnica DN 12 - mesing

