


## Spojnice DN12mm Serija C0.12-B




|                      |                                                                                  |
|----------------------|----------------------------------------------------------------------------------|
| Konstrukcija         | Utičnice spojnice i utikači spojnice, jednosmerno zatvaranje                     |
| Nazivni prečnik      | DN12mm                                                                           |
| Priključak           | G1/2"...G3/4" prema ISO228/1                                                     |
| Materijali           | Telo, ventil i konektor Mesing, Opruga od nerđajućeg čelika 1.4310, Zaptivka NBR |
| Nominalni protok     | 4000NI/min pri 6 bar ( $\Delta p$ 1bar)                                          |
| Medij                | Komprimovani vazduh i tečnosti                                                   |
| Temperatura medijuma | -10...+50°C                                                                      |
| Radni pritisak       | 0...16bar                                                                        |


### C0C12-M Utičnica spojnice - Spoljašnji navoj

|  | D1    | D2 | L1 | L2 | CH | Tip         |
|-------------------------------------------------------------------------------------|-------|----|----|----|----|-------------|
|                                                                                     | G1/2" | 50 | 12 | 82 | 30 | C0C12-M12-B |
|                                                                                     | G3/4" | 50 | 12 | 82 | 30 | C0C12-M34-B |
|                                                                                     |       |    |    |    |    |             |


### C0C12-F Utičnica spojnice - Unutrašnji navoj

|  | D1    | D2 | L1 | L2 | CH | Tip         |
|-------------------------------------------------------------------------------------|-------|----|----|----|----|-------------|
|                                                                                     | G1/2" | 50 | 12 | 82 | 30 | C0C12-F12-B |
|                                                                                     | G3/4" | 50 | 12 | 82 | 30 | C0C12-F34-B |
|                                                                                     |       |    |    |    |    |             |

### C0C12-H Utičnica spojnice - Nastavak za crevo

|  | Unutrašnji prečnik creva |  | L1 | Tip         |
|-------------------------------------------------------------------------------------|--------------------------|--|----|-------------|
|                                                                                     | 13                       |  | 87 | C0P12-H13-B |
|                                                                                     | 16                       |  | 87 | C0P12-H16-B |
|                                                                                     | 19                       |  | 87 | C0P12-H19-B |

### C0P12-M Priključni utikač - Spoljašnji navoj

|  | D1    | L1 | CH | Tip         |
|-------------------------------------------------------------------------------------|-------|----|----|-------------|
|                                                                                     | G1/4" | 54 | 17 | C0P12-M14-B |
|                                                                                     | G1/2" | 63 | 20 | C0P12-M12-B |
|                                                                                     |       |    |    |             |



Ilustracije neobavezujuće  
Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Spojnice / čep spojnice standard / spojnica DN 12 - mesing

