

Male elbow screw-in fitting Series C-WE-R



Basic body with nut and cutting ring






B4 -Cutting ring



B3 -Cutting ring

Design type	Compression fitting with cutting ring, with B3 or B4 cutting ring
Male thread	3/4...1 1/2" BSP, with elastic seal
Tube outside diameter	22...42mm
Material	Galvanized steel
according to standard	EN ISO 8434-1 (DIN 2353)
Medium	neutral liquids and gases that do not attack the materials used
Medium temperature	B3-Cutting ring -40...+120°C B4-Cutting ring NBR -35...+100°C (FKM on request)
Operating pressure	Nominal pressure according to table

Dimensions

								
Main body			with B4 cutting ring			with B3 cutting ring		

Series	PN [bar]	Tube diameter	G	L1	L2	L3	L4	L5	CH1	CH2	Type Main body	Type B4 ring	Type B3 ring
L	160	22	3/4	35	27,5	43,5	15	44	27	36	C-WE22LRX	C-WE22ZLR	C-WE22R
		28	1	38	30,5	49	17	47	36	41	C-WE28LRX	C-WE28ZLR	C-WE28R
		35	1 1/4	45	34,5	57	19	56	41	50	C-WE35LRX	C-WE35ZLR	C-WE35R
		42	1 1/2	51	40	64	20	63	50	60	C-WE42LRX	C-WE42ZLR	C-WE42R
S	400	20	3/4	37	26,5	43,5	15	48	27	36	C-WE20LRX	C-WE20ZLR	C-WE20R
		25	1	42	30	49	17	54	36	46	C-WE25LRX	C-WE25ZLR	C-WE25R
		30	1 1/4	49	35,5	57	19	62	41	50	C-WE30LRX	C-WE30ZLR	C-WE30R
	315	38	1 1/2	57	41	64	20	72	50	60	C-WE38LRX	C-WE38ZLR	C-WE38R

Illustrations non-binding

Design, dimensional and material changes reserved

